

Novel Super-Pitch, Circular Rake, Cambered, Zero-Velocity-Sump Propeller Design Performance Evaluated as a Function of Number of Blades

Robert W. Higbee¹, Wojciech Wyczalkowski¹, Binxin Wu¹

¹ Philadelphia Mixing Solutions Ltd., 1221 East Main Street, Palmyra, PA, 17078 USA

ABSTRACT

Propellers borrowed from the world of marine propulsion are not optimized for use with mixers. Marine props are optimized for a given inlet fluid flow and are designed to optimize thrust whereas mixer props must be designed to achieve a desired flow rate and velocity profile. This presentation discusses a second generation *super-pitch* propeller design that is optimized for the mixing condition where the prop diameter is small compared to the diameter of the mixing vessel such that the fluid velocity at the prop leading edge equals that associated with fluid drawn from a stationary sump. Design goals - Maximize pumping & outlet fluid velocity for a given prop diameter, minimize power consumption, minimize production cost, and minimize overall prop diameter for insertion into standard manholes. Prop design employs the novel, patent pending, concept of circular rake, along with the established concepts of helical profile, 2nd order camber, and skew. The effective pitch-to-diameter ratio at a given point on the leading edge varies with respect to the radius and has been tailored to match the slope of the incoming fluid vector which accounts for both the apparent fluid velocity due to impeller rotation as well as the velocity profile of the incoming fluid. Effective trailing edge pitch-to-diameter ratio was set to a magnitude commonly known as super-pitch. A series of (3) Ø8 inch prop CAD models were created using PTC Pro/Engineer software to explore the relationship between three, four and five evenly spaced propeller blades. All other geometry was held constant. CAD Models were rendered in glass filled nylon using the selective laser sintering (SLS) rapid prototype process. Performance of CAD models was simulated using power consumption formulas derived from an energy perspective and implemented in Mathcad. Structural integrity was determined using Pro/Mechanica (FEA). Fluent computational fluid dynamics (CFD) analysis was used to verify inlet flow field hypothetical shape. The performance (power number N_p and pumping number N_q) was evaluated using a digital torque arm & tachometer and a Dantec laser based particle image velocimetry (PIV).

keywords: propeller, circular rake, mixing, pumping, PIV

Presenting Author's Information:

Name: Robert Higbee

Address: 1221 E. Main Street, Palmyra, PA 17111, USA
Phone number: 717 832 - 8854
e-mail address: bhigbee@philamixers.com

Contact Author's Information:

Name: Wojciech Wyczalkowski
Address: 1221 E. Main Street, Palmyra, PA 17111, USA
Phone number: 717 832 - 8859
e-mail address: wwyczalkowski@philamixers.com

Contact Author's Information:

Name: Binxin Wu
Address: 1221 E. Main Street, Palmyra, PA 17111, USA
Phone number: 717 832 - 8857
e-mail address: bwu@philamixers.com

Please specify whether you wish to be considered for an oral ☐ or poster ☒ presentation.

Do you anticipate submitting a full paper to the special Mixing issue of the Canadian Journal of Chemical Engineering? Yes Maybe **No**